

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :	
Product line : W22 IE3 Three-Phase	Product code : 12862428
Frame : 80 Insulation class : F Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Design : N	Cooling method : IC411 - TEFC Mounting : B5T Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ³ : 15.2 kg Moment of inertia (J) : 0.0009 kgm ²
Output [kW]	1.1
Poles	2
Frequency [Hz]	50
Rated voltage [V]	220/380
Rated current [A]	4.16/2.41
L. R. Amperes [A]	27.5/15.9
LRC [A]	6.6
No load current [A]	1.90/1.10
Rated speed [RPM]	2815
Slip [%]	6.17
Rated torque [Nm]	3.73
Locked rotor torque [%]	330
Breakdown torque [%]	290
Service factor	1.00
Temperature rise	80 K
Locked rotor time	30s (cold) 17s (hot)
Noise level ²	59.0 dB(A)
Efficiency (%)	25%
	50%
	75%
	100%
Power Factor	25%
	50%
	75%
	100%
Losses at normative operating points (speed;torque), in percentage of rated output power	
Losses (%)	P1 (0,9;1,0)
	P2 (0,5;1,0)
	P3 (0,25;1,0)
	P4 (0,9;0,5)
	P5 (0,5;0,5)
	P6 (0,5;0,25)
	P7 (0,25;0,25)
Drive end : 6204 ZZ Non drive end : 6203 ZZ Sealing : Oil Seal Lip Seal Lubrication interval : - Lubricant amount : - Lubricant type : Mobil Polyrex EM	Foundation loads Max. traction : 323 N Max. compression : 473 N
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.	
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.	
Rev.	Changes Summary
Performed by	Performed
Checked by	Checked
Date	29/08/2023
Page	1 / 2
Revision	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	29/08/2023		2 / 2	