

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line : W22 IE3 Three-Phase	Product code : 12862423			
Frame : 63 Insulation class : F Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Design : N	Cooling method : IC411 - TEFC Mounting : B5T Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ² : 7.8 kg Moment of inertia (J) : 0.0002 kgm ²			
Output [kW]	0.18			
Poles	2			
Frequency [Hz]	50			
Rated voltage [V]	220/380			
Rated current [A]	0.955/0.553			
L. R. Amperes [A]	4.97/2.88			
LRC [A]	5.2			
No load current [A]	0.674/0.390			
Rated speed [RPM]	2835			
Slip [%]	5.50			
Rated torque [Nm]	0.607			
Locked rotor torque [%]	260			
Breakdown torque [%]	290			
Service factor	1.00			
Temperature rise	80 K			
Locked rotor time	39s (cold) 22s (hot)			
Noise level ²	52.0 dB(A)			
Efficiency (%)	25%			
	50%			
	75%			
	100%			
Power Factor	25%			
	50%			
	75%			
	100%			
Losses at normative operating points (speed;torque), in percentage of rated output power				
Losses (%)	P1 (0,9;1,0)			
	P2 (0,5;1,0)			
	P3 (0,25;1,0)			
	P4 (0,9;0,5)			
	P5 (0,5;0,5)			
	P6 (0,5;0,25)			
	P7 (0,25;0,25)			
Bearing type : Drive end 6201 ZZ Non drive end 6201 ZZ Sealing : Oil Seal Lip Seal Lubrication interval : - - Lubricant amount : - - Lubricant type : Mobil Polyrex EM	Foundation loads Max. traction : 44 N Max. compression : 121 N			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	29/08/2023		1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	29/08/2023		2 / 2	