

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line : W22 IE3 Three-Phase	Product code : 12862439			
Frame : 180M Insulation class : F Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Design : N	Cooling method : IC411 - TEFC Mounting : B5T Rotation <sup>1</sup> : Both (CW and CCW) Starting method : Direct On Line Approx. weight <sup>2</sup> : 185 kg Moment of inertia (J) : 0.0968 kgm <sup>2</sup>			
Output [kW]	22			
Poles	2			
Frequency [Hz]	50			
Rated voltage [V]	380/660			
Rated current [A]	41.4/23.8			
L. R. Amperes [A]	344/198			
LRC [A]	8.3			
No load current [A]	14.0/8.06			
Rated speed [RPM]	2955			
Slip [%]	1.50			
Rated torque [Nm]	71.1			
Locked rotor torque [%]	290			
Breakdown torque [%]	290			
Service factor	1.00			
Temperature rise	80 K			
Locked rotor time	16s (cold) 9s (hot)			
Noise level <sup>2</sup>	67.0 dB(A)			
Efficiency (%)	25%			
	50%			
	75%			
	100%			
Power Factor	25%			
	50%			
	75%			
	100%			
Losses at normative operating points (speed;torque), in percentage of rated output power				
Losses (%)	P1 (0,9;1,0)			
	P2 (0,5;1,0)			
	P3 (0,25;1,0)			
	P4 (0,9;0,5)			
	P5 (0,5;0,5)			
	P6 (0,5;0,25)			
	P7 (0,25;0,25)			
Bearing type : Drive end 6311 ZZ C3 Non drive end 6211 ZZ C3 Sealing : Oil Seal Lip Seal Lubrication interval : - - Lubricant amount : - - Lubricant type : Mobil Polyrex EM	Foundation loads Max. traction : 2219 N Max. compression : 4036 N			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	30/08/2023		1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	30/08/2023		2 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	30/08/2023			