

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :	
Product line : W22 IE3 Three-Phase	Product code : 12868106
Frame : 132S Insulation class : F Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Design : N	Cooling method : IC411 - TEFC Mounting : B5T Rotation <sup>1</sup> : Both (CW and CCW) Starting method : Direct On Line Approx. weight <sup>2</sup> : 64.0 kg Moment of inertia (J) : 0.0180 kgm <sup>2</sup>
Output [kW]	5.5
Poles	2
Frequency [Hz]	50
Rated voltage [V]	380/660
Rated current [A]	10.8/6.22
L. R. Amperes [A]	85.3/49.1
LRC [A]	7.9
No load current [A]	3.70/2.13
Rated speed [RPM]	2935
Slip [%]	2.17
Rated torque [Nm]	17.9
Locked rotor torque [%]	210
Breakdown torque [%]	290
Service factor	1.00
Temperature rise	80 K
Locked rotor time	21s (cold) 12s (hot)
Noise level <sup>2</sup>	63.0 dB(A)
Efficiency (%)	25%
	50%
	75%
	100%
Power Factor	25%
	50%
	75%
	100%
Losses at normative operating points (speed;torque), in percentage of rated output power	
Losses (%)	P1 (0,9;1,0)
	P2 (0,5;1,0)
	P3 (0,25;1,0)
	P4 (0,9;0,5)
	P5 (0,5;0,5)
	P6 (0,5;0,25)
	P7 (0,25;0,25)
Bearing type : Drive end 6308 ZZ Non drive end 6207 ZZ Sealing : Oil Seal Lip Seal Lubrication interval : - - Lubricant amount : - - Lubricant type : Mobil Polyrex EM	Foundation loads Max. traction : 728 N Max. compression : 1355 N
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.	
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.	
Rev.	Changes Summary
Performed by	Performed
Checked by	Checked
Date	Date
30/08/2023	
Page	Revision
1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	30/08/2023		2 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		Revision
Checked by				
Date	30/08/2023			